

Public Address System

Booster Amplifier


QSB-612E/QSB-624E/QSB-636E/QSB-648E



QSB-624E



QSB-648E



Model	QSB-612E	QSB-624E	QSB-636E	QSB-648E
Power Output (RMS)	120W	240W	360W	480W
Power Supply	AC 115/230V 50/60Hz, DC 24V			
Total Harmonic Distortion	≤ 1 % @ 1 KHz			
Sensitivity	XLR, Phone Jack (Balanced) 1V, 100mV@ 10K Ω			
Output	100 V, 70 V, 8 Ω			
Signal to Noise Ratio	86 dB			
Indicator	Power On, Level			
AC Power Consumption	320W	640W	960W	1280W
DC Power Consumption	8A	15A	24A	30A
Dimension (H x W x D)	88 x 425 x 305 mm		132 x 425 x 355 mm	
Weight	8.2 KGS	10.6 KGS	15 KGS	17 KGS
Mounting	FREE STANDING OR 19" RACK			

Features:

- ☐ Easy to Use.
- ☐ One XLR / Phone Jack Input
- ☐ One XLR / Phone Jack Output
- ☐ 2 power sources: DC 24V and AC 230/115V 50/60Hz
- ☐ Over temperature, over load, and speaker short protection.
- ☐ Sensitivity selection Switch
- ☐ Speaker output : 8 Ω, 70V and 100V.
- ☐ Standard 19" rack model.