

Sound Processor HTM-1/SRHA-6

Model	HTM-1
Power Supply	DC 12V
Video Input	Bypass
Total Harmonic Distortion	<0.02%
Audio Sensitivity	Audio in 300mV
Audio Output	300mV
MIC Sensitivity	10mV (Volume Max.)
MIC Frequency Response	50 ~ 2K Hz $\pm$ 2 dB
PC Power Consumption	100 mV @ Rated Power
Dimension	45 (H) x 143(W) x 93 (D) mm
Weight	0.5 KGS
Mounting	Free Mounting

MIC Echo Amplifier HTM-1



Stereo Headphone Amplifier SRHA-6

Model	SRHA-6
Power Supply	AC 115/230v 60/50 Hz
Total Harmonic Distortion	< 0.008%
Max. Level	+18 dBV (Unbalanced)
Signal to Noise Ratio	>90 dB
Frequency Response	20 Hz ~ 30K Hz $\pm$ 1dB
Input Impedance	100K Ω (Unbalanced)
Input connector	1/4" Phone Jack Stereo (Unbalanced) R&L 1/4" Phone Jack Unbalanced Aux Input 1/4" Phone Jack Insert Jack
IMD(SMPTE)	<0.008%
Max. Output Power	Up to 300mW/Channel
Dimension	44 (H) x 483 (W) x 130 (D) mm
Weight	2.1 KGS
Mounting	19" Rack