

Sound Processor

SRSE-100/SRCX-22/SRCX-23

Model	SRSE-100
Power Supply	AC 115/230V 60/50Hz
Nominal Operating Level	-10 dB ~ 4 dBu
Total Harmonic Distortion	< 0.005% @ 4 dBu
Max. Level	21 dBu (Unbalanced)
Noise & Hum. Unity Gain	94 dBu
Band Width	10~50KHz +0/-1dB
Input Impedance	20K Ω (Unbalanced) 1/4" Phone Jack 20K Ω (Unbalanced) RCA
Output Impedance	100K Ω (Unbalanced) 1/4" Phone Jack 100K Ω (Unbalanced) RCA
IM Distortion	<0.01% @ 4 dBu(Smpte)
Crosstalk	> 83 dBu @ 20K Hz
Dimension	44 (H) x 483 (W) x 130 (D) mm
Weight	2.2 KGS
Mounting	19" RACK

Sound Enhancement processor SRSE-100



Crossover - Stereo



2 Way with Subwoofer SRCX-22

3 Way with Subwoofer SRCX-23

Model	SRCX-22	SRCX-23
Power Supply	AC 115/230V 60/50Hz	
Crossover Range	50 ~ 250 Hz, -24/10 dB (Subwoofer) 250 ~ 6K Hz, -24/10 dB (Low/High)	50 ~ 250 Hz, -24/10 dB (Subwoofer) 70 ~ 1K Hz, -24/10 dB (Low/High) 480 ~ 7K Hz, -24/10 dB (Mid/High)
Total Harmonic Distortion	<= 0.05%	
Filter Type (Slope)	2nd Order, 12 dBu/Octave	
Signal to Noise Ratio	> 95 dB	>= 80 dB
Frequency response	20~25KHz $\pm$ 1dB	
Input Impedance	100K Ω (Unbalanced) 1/4" phone jack 95K Ω (Balanced) XLR	100K Ω (Unbalanced) 1/4" phone jack 50K Ω (Balanced) XLR
Output Impedance	200 Ω (Unbalanced) 1/4" Phone Jack	200 Ω (Unbalanced) 1/4" XLR
Low Cut Filter	30 Hz/-3 dB, 12 dB/Octave	
Dimension	44 (H) x 483 (W) x 130 (D) mm	
Weight	2.3 KGS	
Mounting	19" RACK	